

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Super Shield Silver Coated Copper Conductive Coating**SDS Code:** 843-Liquid**Related Part #** 843-20G, 843-900ML, 843-1G

Recommended Use and Restriction on Use

Use: Electrically conductive coating and EMI/RFI shield**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidentsUSA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Section 2: Hazard(s) Identification




Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Reproductive Toxicity	2	Warning	Health
Specific Target Organ Toxicity Repeated Exposure	2	Warning	Health
Skin Irritation	2	Warning	Exclamation
Eye Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation
Environmental Hazard Chronic Aqua. Tox.	1	Warning	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements


Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapour
	H373: May cause damage to organs (inner ear or central nervous system) through prolonged or repeated exposure H361: Suspected of damaging fertility or the unborn child
	H315: Causes skin irritation H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Continued...

Pictograms	Hazard Statements
	H410: Very toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof equipment.
P243	Take action to prevent static discharges.
P260 + P271	Do not breathe mist/vapors/spray. Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IN ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING
843-LIQUID
Continued...

Response	Precautionary Statements
P337 + P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	<i>None</i>	<i>None</i>
Argyria	Long term exposure to silver powder or compounds can lead to an irreversible blue-grey discoloration of the skin.	<i>None</i>	<i>None</i>

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-50-8	copper	43%
108-88-3	toluene	13%
67-64-1	acetone	8%
7440-22-4	silver	5%
110-19-0	isobutyl acetate	4%
110-43-0	heptan-2-one ^{a)}	4%
64-17-5	ethanol	3%
141-78-6	ethyl acetate	2%
108-65-6	1-methoxy-2-propanol acetate	1%

a) Also known as methyl amyl ketone (MAK)

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN	P303 + P361 + P353, P332 + P313, P363
Immediate Symptoms	<i>redness, irritation, dry skin</i>
Response	Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
IF INHALED	P304 + P340 + P312, P308 + P313
Immediate Symptoms	<i>drowsiness, dizziness, cough, headaches, nausea, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>irritation, redness, pain</i>
Response	Rinse cautiously with water for 15 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>nausea, sore throat, diarrhea, drowsiness, dizziness</i>
Response	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion. Prevent fire-fighting wash from entering waterway or sewer system.

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID**

Combustion Products Produces carbon oxides (CO,CO₂) and metal oxide fumes.

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

Precautions for Response Do not breathe the mist/spray/vapors. Remove or keep away all sources of extreme heat or open flames.

Environmental Precautions Avoid releasing to the environment. Prevent spill from entering drains and waterways.

Containment Methods Contain with inert absorbent (such as soil, sand, vermiculite).

Cleaning Methods Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.

Disposal Methods Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.

Do not breathe mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Ground and bond container and receiving equipment.

Use explosion-proof equipment.

Take action to prevent static discharges.

Do not eat, drink, or smoke when using this product.

Handling Wear protective gloves/clothing/eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Avoid release to the environment. Collect spillage.

Storage Keep container tightly closed.

Store in well-ventilated place. Keep cool.

Store locked up.

SILVER COATED COPPER CONDUCTIVE COATING
843-LIQUID
Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
copper <i>(dust and mist)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1.0 mg/m ³ 1.0 mg/m ³ 1 mg/m ³ 1.0 mg/m ³ 1 mg/m ³ 1 mg/m ³	Not established Not established Not established Not established Not established Not established
toluene	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	20 ppm 200 ppm 50 ppm 20 ppm 20 ppm 100 ppm	Not established 300 ppm Not established Not established Not established 150 ppm
acetone	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm 1 000 ppm 500 ppm 250 ppm 500 ppm 750 ppm	750 ppm Not established 750 ppm 500 ppm 750 ppm 1 000 ppm
silver <i>(metal dust, mist)</i> <i>(metal)</i> <i>(Ag and its compounds)</i> <i>(metal, dust, fumes)</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	0.1 mg/m ³ 0.01 mg/m ³ 0.1 mg/m ³ 0.01 mg/m ³ 0.1 mg/m ³ 0.1 mg/m ³	Not established Not established Not established 0.03 mg/m ³ Not established Not established
isobutyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	150 ppm 150 ppm 150 ppm 150 ppm 150 ppm 150 ppm	Not established Not established Not established Not established Not established Not established
heptan-2-one <i>methy amyl ketone</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	50 ppm 100 ppm 50 ppm 50 ppm 25 ppm 50 ppm	Not established Not established Not established Not established Not established Not established

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Continued...

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
ethanol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	Not established 1 000 ppm 1 000 ppm Not established Not established 1 000 ppm	1 000 ppm Not established Not established 1 000 ppm 1 000 ppm Not established
ethyl acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	400 ppm 400 ppm 400 ppm 150 ppm 400 ppm 400 ppm	Not established Not established Not established Not established Not established Not established
1-methoxy-2-propanol acetate	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	Not established 50 ppm Not established 50 ppm 50 ppm Not established	Not established Not established Not established 75 ppm Not established Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.
Recommendation: Ensure that glasses have side shields for lateral protection.

Skin Protection For incidental contacts, use nitrile, neoprene, PVC gloves, or other chemically resistant gloves.
For likely contacts, use of protective butyl rubber, fluorinated rubber, or other chemically resistant gloves.

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING
843-LIQUID

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{b)}	1%
Appearance	Light brown metallic	Upper Flammability Limit ^{b)}	12%
Odor	Benzene like, sweetish	Vapor Pressure ^{b)} @20 °C	69 hPa [52 mmHg]
Odor Threshold ^{a)}	2 ppm	Vapor Density	2.0 to 4.6 (Air =1)
pH	7	Specific Gravity @25 °C	1.67
Freezing/Melting Point	Not available	Solubility in Water	Partially soluble
Boiling Point ^{a)}	56 °C [132 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	-17 °C [1.4 °F]	Auto-ignition Temperature ^{c)}	≥315 °C [≥599 °F]
Evaporation Rate	Fast	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity ^{d)} @40 °C	≥34 mm ² /s

a) Values based on acetone component.

b) Lower and Upper Explosive Limits, and vapor pressure of mixture calculated using Le Chatelier principle and component physical values.

c) The auto-ignition value is based on 1-methoxy-2-propanol acetate, which is the component with the lowest value.

d) Kinematic viscosity at 40 °C for separation layer

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID****Section 10: Stability and Reactivity**

Reactivity	The copper may form shock sensitive compounds in the presence of acetylenic compounds.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, open flames, and incompatible substances
Incompatibilities	Oxidizing agents, strong acids, peroxides, acetylenic compounds
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information**Routes of Exposure**

Inhalation, Eye contact, Skin contact, and Ingestion

Symptoms Summary

Eyes	Causes redness, severe irritation, and pain.
Skin	Causes skin redness, irritation, and dry skin.
Inhalation	May cause drowsiness, dizziness, cough, headaches, nausea, or unconsciousness.
Ingestion	May cause nausea, sore throat, and diarrhea (see inhalation symptoms).
Chronic	<p>Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin. Exposure to silver powder may also cause argyria, an irreversible blue-grey discoloration of the skin.</p> <p>Chronic inhalation exposure may effect the central nervous system and lead to hearing loss with co-exposure to loud noises.</p> <p>Ingestion or inhalation of paint material, mist, or vapor during pregnancy may increase the chances fetal death and developmental defects.</p>

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING
843-LIQUID
Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
copper	>5 000 mg/kg Mouse	Not available	Not available
toluene	636 mg/kg Rat	12 124 mg/kg Rabbit	49 g/m ³ 4h Rat
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit ^{a)}	16 000 ppm 6h Rat
silver	>5 g/kg Guinea Pig	Not available	Not available
isobutyl acetate	13 400 mg/kg Rat	>17 400 mg/kg Rabbit	>13.24 mg/L 6 h Rat
heptan-2-one	1 670 mg/kg Rat	12 600 µL/kg Rabbit	Not available
ethanol	7 060 mg/kg Rat	Not available	20 000 ppm 10 h Rat
ethyl acetate	5 620 mg/kg Rat	>20 000 µL/kg Rabbit	45 g/m ³ 2 h Mouse
1-methoxy-2-propanol acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier (M)SDS were also consulted.

a) Supplier MSDS

Other Toxicological Effects
Skin corrosion/irritation

Toluene is a known serious skin irritant.

Serious eye damage/irritation

Acetone and ethanol are known serious eye irritants.

Sensitization
(allergic reactions)

Based on available data, the classification criteria are not met.

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID****Carcinogenicity**

(risk of cancer)

Evidence of carcinogenicity of ethanol relates to excessive alcoholic beverage consumption, and doesn't relate to exposure risks when used in the workplace or as a non-comestible consumer product.

Ethanol [64-17-5]

IARC Group 1: Carcinogenic to human when consumed as beverage.

ACGIH A3: Confirmed animal carcinogen with unknown relevance to humans

CA Prop 65: Listed as a carcinogen when consumed as a beverage

NTP: Not listed

Mutagenicity

(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity

(risk to sex functions)

Toluene and ethanol present reproductive and developmental hazards at high doses (>13,000 µg/day)

Teratogenicity (risk of fetus malformation)

Harmful to unborn fetus

STOT-single exposure

Acetone, toluene, isobutyl acetate, 2-heptanone, ethyl acetate, and 1-methoxy-2-propanol acetate can affect the central nervous system by inhalation causing drowsiness or dizziness.

STOT-repeated exposure

Contains 13% toluene, which is a Cat 2 STOT repeated exposure hazard for the central nervous system and cochlear systems. Toluene is ototoxic chemicals according to rat studies: inhalation exposure in the presence of noise may lead to cochlear impairment.

Aspiration hazard

Based on available data, the classification criteria are not met. There is less than 10% category 1 components, and the kinematic viscosity is >20.5 mm²/s at 40 °C.

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains silver and copper particles of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver and ionic copper levels that are very toxic to the environment. While massive silver and copper are insoluble in water, their powders are considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic aqueous toxicity of category 1 (M = 10 for silver and M = 1 for copper) of the EU.

Toluene is an acute category 2 environmental toxicant (with minimal LC50 of 7.63 mg/L for *Oncorhynchus mykiss* (rainbow trout); 8.9 mg/L 24 h *Daphnia magna* (water flea); 10 mg/L 24 h *Pseudokirchneriella subcapitata* (green algae)).

Acetone, isobutyl acetate, heptan-2-one, ethanol, ethyl acetate, and 1-methoxy-2-propanol acetate are not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

- Acetone has a minimal LC50 96 h of 5 540 mg/L for *Oncorhynchus mykiss* (rainbow trout) and an EC50 48 h of 13 500 mg/L for *Daphnia magna* (water flea).
- Isobutyl acetate as a minimal LC50 48 h of 101 mg/L for *Leuciscus idus melanotus* and 250 mg/L for *Daphnia magna* (water flea).
- Heptan-2-one has a minimal LC50 96 h of 126 mg/L for *Pimephales promelas* (fathead minnow).
- Ethanol is biodegradable and has a minimal LC50 of >1 000 mg/L for fish, invertebrates, and algae.
- Ethyl acetate has a minimal LC50 of ≥ 220 mg/L 96 h for *Pimephales promelas* (fathead minnow); 2 300 mg/L 24 h *Daphnia magna* (water flea); 4 200 mg/L 72 h green algae.
- 1-Methoxy-2-propanol has a minimal LC50 96 h of ≥ 100 mg/L *Salmo gairdneri*.

Acute Ecotoxicity

Category 1

Very toxic to aquatic life

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Biodegradability

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Other Effects

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

VOC = 27% [466 g/L]




Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

<p>Sizes 5 L and under</p> <p>Limited Quantity</p> <div style="text-align: center; margin-top: 20px;">  </div>	<p>Sizes greater than 5 L</p> <p>UN number: UN1263 Shipping Name: PAINT Class: 3 Packing Group: II Marine Pollutant: Yes</p> <div style="text-align: right; margin-top: 20px;">   </div> <p style="text-align: center; margin-top: 20px;">Flash Point \geq -17 °C [1.4 °F]</p>
--	--

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 1 L and under

Limited Quantity



Sizes up to 5 L (passenger), 60 L (cargo)

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: Yes



Flash Point \geq -17 °C [1.4 °F]

Sea

Refer to IMDG regulations.

Sizes 5 L and under

Limited Quantity



Sizes greater than 5 L

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: Yes



Flash Point \geq -17 °C [1.4 °F]

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

SILVER COATED COPPER CONDUCTIVE COATING

843-LIQUID

Section 15: Regulatory Information

Canada

WHMIS 1988 Classification



B2 – Flammable Liquid;

D2A – Very Toxic (Reproductive Toxicity/Embryotoxicant);

D2B – Toxic Other (Skin and Eye Irritant)

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.


USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains toluene, which is listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains toluene (CAS# 108-88-3; reportable quantity = 1000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains acetone (CAS# 67-64-1), and isobutyl acetate (CAS# 110-19-0), which are subject to the CERCLA reporting requirements at the 5000 lb (2268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product contains toluene, which is listed as reproductively toxic.

This product contains ethanol, which is listed as reproductively toxic. It is also listed as a carcinogen when in an alcoholic beverage.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by Michel Hachey

Date of Review 23 November 2015

Supersedes 17 April 2013

Reason for Changes: Compliance adjustments to meet both HCS2012 and WHMIS 2015 regulations.

Section continued on the next page

SILVER COATED COPPER CONDUCTIVE COATING**843-LIQUID****Reference**

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.