

834B-A

**BLACK FLAME RETARDANT EPOXY**

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Name:** 834B-A**Other Product Identifier:** Black Flame Retardant Epoxy**Related Part #** 834B-375ML, 834B-2.7L, 834B-10.8L, 834B-60L

### Recommended Use and Restriction on Use

**Use:** Resin for use with epoxy hardener**Uses Advised Against:** Not for use as spray coating

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number




**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)USA or CANADA—Call CHEMTREC at **+1-800-424-9300****For emergencies involving the transport of dangerous goods;** 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**Section 2: Hazard(s) Identification**
**Classification of the Chemical Material**
**GHS Categories**

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Reproductive Toxicity	Oral	2	Warning	Health
Hazardous to the Aquatic Environment	Chronic	2	<i>none</i>	Environment

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H317: May cause an allergic skin reaction H315: Causes skin irritation H319: Causes serious eye irritation
	H361: Suspected of damaging fertility or the unborn child
	H411: Toxic to aquatic life with long lasting effects

*Section continued on the next page*

**834B-A**

**BLACK FLAME RETARDANT EPOXY**

*Continued...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing fumes/vapors.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P391	Collect spillage.
<b>Storage</b>	<b>Precautionary Statements</b>
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents/container in accordance to local/regional/international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
None	None	None	None

**834B-A**
**BLACK FLAME RETARDANT EPOXY**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	% (weight)
25085-99-8	bisphenol-A-(epichlorhydrin)	30%
21645-51-2	aluminum trihydrate	21%
68333-79-9	ammonium polyphosphate	19%
1344-28-1	aluminum oxide	16%
17557-23-2	neopentyl glycol diglycidyl ether	6%
138265-88-0	zinc borate	5%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin)	1%
1333-86-4	carbon black	0.4%

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF IN EYES</b>	P305 + P351 + P338
<b>Immediate Symptoms</b>	<i>redness, irritation, pain</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>IF ON SKIN</b>	P302 + P352, P333 + P313, P362 + P364
<b>Immediate Symptoms</b>	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
<b>Response</b>	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
<b>IF INHALED</b>	P304 + P340
<b>Immediate Symptoms</b>	<i>cough, irritation of the respiratory track</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.
<b>IF SWALLOWED</b>	P301 + P330, P331, P308 + P313
<b>Immediate Symptoms</b>	<i>nausea, vomiting, diarrhea, burns or irritation to the digestive tract</i>
<b>Response</b>	Rinse mouth. Do not induce vomiting. IF exposed or concerned: Get medical advice/attention.

**834B-A****BLACK FLAME RETARDANT EPOXY****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use extinguishing media suitable for surrounding materials.
<b>Specific Hazards</b>	Not flammable or combustible, but will burn if involved in a fire. Produces irritating smoke of unknown toxicity in fires.  Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), zinc oxides, boron oxides, ammonia and other toxic fumes.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing the fumes/vapors. Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).

*Section continued on the next page*

**834B-A**

**BLACK FLAME RETARDANT EPOXY**

**Cleaning Methods** Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.

**Disposal Methods** Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

**Prevention** Keep out of reach of children.  
 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Avoid breathing fumes/vapors.  
 Avoid release to the environment.

**Handling** Wear protective gloves/protective clothing/eye protection/face protection.  
 Take off contaminated clothing and wash it before reuse.  
 Wash hands thoroughly after handling.  
 Collect spillage.

**Storage** Store locked up.

**Section 8: Exposure Controls/Personal Protection**

**Substances with Occupational Exposure Limit Values**

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds <sup>a)</sup>	ACGIH	1 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	15 mg/m <sup>3</sup>	Not established
	Canada AB	10 mg/m <sup>3</sup>	Not established
	Canada BC	1 mg/m <sup>3</sup>	Not established
	Canada ON	1 mg/m <sup>3</sup>	Not established
	Canada QC	10 mg/m <sup>3</sup>	Not established

*Section continued on the next page*

**834B-A**
**BLACK FLAME RETARDANT EPOXY**

Continued...

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminium oxide	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	5 mg/m <sup>3</sup>	Not established
	Canada AB	10 mg/m <sup>3</sup>	Not established
	Canada BC	Not established	Not established
	Canada ON	Not established	Not established
	Canada QC	10 mg/m <sup>3</sup>	Not established
carbon black <sup>a)</sup>	ACGIH	3.5 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	3.5 mg/m <sup>3</sup>	Not established
	Canada AB	3.5 mg/m <sup>3</sup>	Not established
	Canada BC	3 mg/m <sup>3</sup>	Not established
	Canada ON	3.5 mg/m <sup>3</sup>	Not established
	Canada QC	3.5 mg/m <sup>3</sup>	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

## Engineering Controls

### Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Because the carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

## Personal Protective Equipment

### Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

### Skin Protection

Wear appropriate protective clothing to prevent skin contact.

**RECOMMENDATION:** Use butyl rubber, neoprene, or other chemically resistant gloves.

*Section continued on the next page*

**834B-A**

**BLACK FLAME RETARDANT EPOXY**

**Respiratory Protection** If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

Generally, for emergencies and exposure above 0.5 mg/m<sup>3</sup>, use a self-contained breathing apparatus with full face piece operated in a pressure positive mode.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not available
<b>Appearance</b>	Black	<b>Upper Flammability Limit</b>	Not available
<b>Odor</b>	Mild	<b>Vapor Pressure @25 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	Not available
<b>pH</b>	Not available	<b>Specific Gravity @25 °C</b>	1.69
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Practically insoluble
<b>Boiling Point</b>	Not available	<b>Partition Coefficient</b>	Not available
<b>Flash Point</b>	Not available	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability (solid, gas)</b>	Not available	<b>Viscosity @25 °C</b>	27 500 cP [16 300 mm <sup>2</sup> /s]



**834B-A**

**BLACK FLAME RETARDANT EPOXY**

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Reacts exothermically with amines.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures.
<b>Conditions to Avoid</b>	Excessive heat, and incompatible substances. Do not use in a way that forms a mist or aerosolize the product.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids, and strong bases.
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**Section 11: Toxicological Information**

**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	May cause severe eye irritation, redness, and pain.
<b>Skin</b>	May cause redness, dry skin, serious skin irritation, and skin sensitization.
<b>Inhalation</b>	May cause cough, and irritation of the respiratory system.
<b>Ingestion</b>	It may cause nausea, vomiting, diarrhea, burns or irritation to the digestive tract.
<b>Chronic</b>	Prolonged and repeated exposure may lead to skin sensitization reactions. Long term exposure to carbon black dust or mist may cause cancer.

**Lethal Exposure Concentrations**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
bisphenol-A-(epichlorhydrin)	>2 000 mg/kg Rat	23 000 mg/kg Rabbit	Not available
aluminum trihydrate	79 000 mg/kg Rat	Not available	Not available
ammonium polyphosphate	300 mg/kg Rat	Not available	Not available
aluminum oxide	Not available	Not available	Not available

*Section continued on the next page*

**834B-A**

**BLACK FLAME RETARDANT EPOXY**

*Continued...*

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
neopentyl glycol diglycidyl ether	Not available	Not available	Not available
zinc borate	10 000 mg/kg Rat	10 000 mg/kg Rat	Not available
reaction product: bisphenol-A- (epichlorhydrin)	>2 000 mg/kg Rat	>2 000 mg/kg Rat	Not available
carbon black	>15 g/kg Rat	>3 g/kg Rabbit	Not available

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier (M)SDSs were also consulted.

**Other Toxicological Effects**

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Causes serious irritation.

**Respiratory and skin sensitization** (allergic reactions)

The epoxy resin components (CAS# 25085-99-8, and 25068-38-6) may cause skin sensitization in humans.

**Carcinogenicity**  
(risk of cancer)

The carbon black is possibly carcinogenic by airborne routes of exposures. Because they are both bound in the epoxy liquid mixture, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal use.

**Carbon Black [1333-86-4]**

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

**Mutagenicity**  
(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

**Reproductive Toxicity**  
(risk to sex functions)

Animal ingestion studies show that high doses of zinc borate cause reproductive and developmental effects.

**Teratogenicity**  
(risk of fetus malformation)

Based on available data, the classification criteria are not met.

*Section continued on the next page*

**834B-A****BLACK FLAME RETARDANT EPOXY**

<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. The kinematic viscosity is >20.5 mm <sup>2</sup> /s at 40 °C.

**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The epoxy resins (CAS# 25085-99-8, and 25068-38-6) have a LC50 for aquatic organisms 1 mg/L to 10 mg/L.

The zinc borate is classified as a chronic category 1 environmental toxicant with a M-Factor of 1 (with minimal LC50 96 h of 2.4 mg/L for *Oncorhynchus mykiss* (rainbow trout); LC50 48 h of 76 mg/L *Daphnia magna* (water flea); and transformation/dissolution endpoint for zinc borate powder that release of 0.452 mg/L of zinc ion, which is higher than zinc's NOEC limit).

Based on available data, ammonium polyphosphate, aluminum trihydrate, aluminum oxide, neopentyl glycol diglycidyl ether and carbon black are not classified as environmental hazards according to GHS criteria.

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Chronic Ecotoxicity**

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not available

**Bioaccumulation**

Not available

**834B-A**

**BLACK FLAME RETARDANT EPOXY**


**Section 13: Disposal Considerations**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

<p>Sizes under 450 L <i>Part A of all 834B kits</i> <b>NOT REGULATED</b> in TDG per Special Provisions 99</p>	<p>49 CFR: Sizes greater than 5 L <i>Part A of 834B-10.8L, 834B-60L kits</i> <b>UN number:</b> UN3082 <b>Shipping Name:</b> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction product: bisphenol-A-(epichlorhydrin)) <b>Class:</b> 9 <b>Packing Group:</b> III <b>Marine Pollutant:</b> Yes</p>
<p>Sizes 5 L and under <i>Part A of 834B-375ML, 834B-2.7L kits</i> <b>NOT REGULATED</b> in 49 CFR per exception 171.4 (c)(2)</p>	

**Special Provision 99 (2):** These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

*Section continued on the next page*

**834B-A**

**BLACK FLAME RETARDANT EPOXY**

**Air**

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 5 L and under:

*Part A of 834B-375ML/2.7L kits*

**NOT REGULATED**

Not Restricted, as per  
Special Provisions A197

Sizes greater than 5 L:

*Part A of 834B-10.8L, 834B-60L kit*

**UN number:** UN3082

**Shipping Name:**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: bisphenol-A-  
(epichlorhydrin))

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes



**Special Provision A197:** These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Sea**

Refer to IMDG regulations.

Sizes 5 L and under:

*Part A of 834B-375ML/3L kits*

**NOT REGULATED**

per 2.10.2.7

Sizes greater than 5 L:

*Part A of 834B-60L kit*

**UN number:** UN3082

**Shipping Name:**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: bisphenol-A-  
(epichlorhydrin))

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes



**2.10.2.7:** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

**Note:** Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


**USA**

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>* 3</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain ingredients that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

*Section continued on the next page*

**834B-A****BLACK FLAME RETARDANT EPOXY****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>MSDS Prepared by</b>	Michel Hachey
<b>Date of Revision</b>	12 October 2017
<b>Supersedes</b>	20 September 2017

**Reason for Changes:** Change to classification based on corrected data.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

*Section continued on the next page*



**834B-A**

**BLACK FLAME RETARDANT EPOXY**

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer** This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.